



## **VIPER 360**

### **Fiber Optic High Speed Handpiece**

Operating Speed: 420,000 rpm  
Stall Torque: 9.0 gf-cm  
Operating Pressure: 38-43 psi  
Air Consumption: 30 l/min  
Head Diameter: 11 mm  
Head Length: 13.9 mm  
OAL Length: 98 mm  
Weight: 52 g



## **VIPER HIT**

### **High Torque F/O High Speed Handpiece**

Operating Speed: 340,000 rpm  
Stall Torque: 12.0 gf-cm  
Operating Pressure: 38-43 psi  
Air Consumption: 32 l/min  
Head Diameter: 13 mm  
Head Length: 14 mm  
OAL Length: 98 mm  
Weight: 52 g



## **VIPER MINI**

### **Mini Head F/O High Speed Handpiece**

Operating Speed: 400,000 rpm  
Stall Torque: 7.6 gf-cm  
Operating Pressure: 38-43 psi  
Air Consumption: 20 l/min  
Head Diameter: 10.3 mm  
Head Length: 8.6 mm  
OAL Length: 101 mm  
Weight: 50 g



## **QUANTUM**

### **Fiber Optic High Speed Handpiece**

Operating Speed: 400,000 rpm  
Stall Torque: 8.5 gf-cm  
Operating Pressure: 38-43 psi  
Air Consumption: 30 l/min  
Head Diameter: 11 mm  
Head Length: 14.8 mm  
OAL Length: 98 mm  
Weight: 53 g



## **VIPER 5H**

### **Fiber Optic High Speed Handpiece**

Operating Speed: 420,000 rpm  
Stall Torque: 8.5 gf-cm  
Operating Pressure: 38-43 psi  
Air Consumption: 20 l/min  
Head Diameter: 11 mm  
Head Length: 13.9 mm  
OAL Length: 115 mm  
Weight: 59 g